Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

, M.

- 1. (Currently Amended) Arrangement for transferring, mixing, and dispensing components that comprises at least two dispensing devices, at least one of the dispensing devices containing at least one liquid component and the arrangement comprising a transfer unit for the connection of the dispensing devices that at least comprises connecting channels between two adjacent or opposite dispensing devices, characterized in that wherein the transfer unit (15, 31, 39) comprises connecting channels (16; 38; 43, 44) between outlets (17, 18; 41, 42) for the components (21, 23; 22, 24) of both dispensing devices (1, 2) and locking members (36) for receiving corresponding locking members (37) on flanges (19, 20) provided on the dispensing devices (1, 2).
- 2. (Currently Amended) Arrangement according to claim 1, characterized in that wherein the connecting channels (16) of the removably attachable transfer unit (15, 39) are configured for transferring the liquid components (21, 23) from one of the dispensing devices (2) to another dispensing device (1) that is arranged in parallel thereto.
- 3. (Currently Amended) Arrangement according to claim 2, eharacterized in that wherein the transfer unit (15) comprises connecting channels (16) between one outlets (17, 18; 41, 42) respectively of one storage containers (5, 7; 6, 8) of the one or the other dispensing device (1, 2).
- 4. (Currently Amended) Arrangement according to claim 1 or 2, characterized in that wherein the transfer unit (39) is adapted for receiving at least two frontally opposite dispensing devices (1, 2), the transfer unit having pairs of through-going connecting channels (43, 44) between the outlets (17, 18; 41, 42) of the dispensing devices (1, 2).
- 5. (Currently Amended) Arrangement according to claim 1, characterized in that wherein the transfer unit (31) comprises connecting channels (38) from the outlets (17, 18;

41, 42) of the dispensing devices (1, 2) to a common coupling (32) having at least one outlet (33, 34) for a mixer (25) or an accessory.

- 6. (Currently Amended) Arrangement according to any one of claims 1 to 5 claim 1, characterized in that wherein at least one of the storage containers (5, 6) comprises a mixing arrangement (4).
- 7. (Currently Amended) Arrangement according to any one of claims 1 to 6 claim 1, characterized in that wherein the dispensing devices are double dispensing devices (1, 2).
- 8. (Currently Amended) Arrangement according to claim 7, eharacterized in that wherein the dispensing devices are double syringes (1, 2) with double thrust rods (9, 10).
- 9. (Currently Amended) Arrangement according to claim 7, characterized in that wherein the dispensing devices are double cartridges with dispensing pistons.
- 10. (Currently Amended) A method for transferring, mixing, and dispensing components by means of an arrangement of elaims 1 to 9 claim 1, characterized in that wherein the dispensing devices are coupled to the transfer unit, the dispensing device (2) for the liquid component is actuated for introducing that component into the other one, and the two components are mixed in another dispensing device (1) and the mixture is dispensed.
- 11. (Currently Amended) The method of claim 10, eharacterized in that wherein the dispensing devices are double dispensing devices (1, 2).